



Hebden & Holding

Glutz Multipoint Door Lock



Glutz 1893 Multipoint Locks

These locks can be used with either lever on rose with separate escutcheon, or a long narrow backplate lever handle set. As the lever only operates the latch a standard sprung lever with 38mm screw centres is ideal.

The euro-profile cylinder will operate the double throw deadlocking and retract the latch. Therefore the lock can operate without a lever handle.

The overall gearbox depth is 94mm.
Centres of 92mm.
Backset 65mm.

Lock GLU-1893.7.1744-65/92

Product profile

Commercial public and private buildings,

Standard version

- Backset PZ 92 mm: 65mm
- Latch blocking with handle free clutch (1st turn)
- 4-part clamp follower, square hole 8mm
- Blue galvanised
- Easy latch withdrawal
- Reversible steel latch knob / can be replaced when not fitted
- Latch head with inclined inlet
- Hardened steel main bolt 8 x 30 mm, deadbolt double throw 2 x 12.5mm
- 2 additional hardened steel bolts 8 x 12mm, deadbolt double throw 2 x 10 mm
- Radiussed forend 20x3 mm
- Recess for safety plate screws
- Chip protection bushing

Part numbers for lock and keeps

GLU-1893.7.1744-65/92	KEY OP. 3 POINT LOCK RAD END 65/92	1 Required
GLU-B-1131	KEEP FOR ADDITIONAL BOLT GALVANIZED	2 Required
GLU-V-1138	S/STAINLESS CENTRE STRIKE ADJ. RH	Either Left
GLU-V-1138/L	S/STAINLESS CENTRE STRIKE ADJ. LH	or Right



Latch/Deadbolt Keep (Handed) GLU-V-1138

Product profile

High strength, adjustable burglar resistant latch and bolt strike plate for flush doors on timber frames.

Standard version

- Satin stainless steel
- 210 x 24 x 3 mm
- Radius 1.5 mm
- Rib 14-17 mm
- Left / right indication necessary

Left Hand
Shown

Options

- Black plastic push-fit box for covering latch and deadbolt mortices

Quality standard

Tested to DIN 18104-2 (burglar resistant upgrade products) and hence can be used with WK2 doors pursuant to ENV 1627-1630

Deadbolt Keep GLU-B-1131

Product profile

High strength, burglar resistant strike plate for deadbolts for rebated doors on timber frames.

Standard version

- Satin stainless steel
- 70 x 20 x 10 mm
- Radius 1.5 mm
- Rib 4 mm
- incl. 2 special screws for concealed skewed fixing
- Left / right

Options

- Black plastic push-fit box for covering latch and deadbolt mortices

Quality standard

Tested to DIN 18104-2 (burglar resistant upgrade products) and hence can be used with WK2 doors pursuant to ENV 1627-1630



Tel:- 01535 602517 - Fax:- 01535 662054

www.hebdenandholding.co.uk

Keighley Industrial Park, Royd Ings Ave, Keighley BD21 4DZ

